

CLAIMS

- Sub
a2
1. A suspension component connection assembly,
comprising:

a suspension component having a bushing
receiving bore with first and second opposing axial
ends, said bushing receiving bore including a groove
portion positioned intermediate said first and second
axial ends of said suspension component; and

a sleeveless bushing having an elastomeric
portion with first and second opposing axial ends,
said elastomeric portion having a ribbed portion
positioned intermediate said first and second axial
ends of said elastomeric portion, said ribbed portion
being adapted to fit within said groove portion of
said suspension component.

2. The suspension component connection assembly of claim
1 wherein said suspension component comprises a leaf
spring and said bushing receiving bore comprises a
leaf spring eye.
3. The suspension component connection assembly of claim
1 wherein said suspension component comprises a
shackle assembly.
4. The suspension component connection assembly of claim
1 wherein said sleeveless bushing further comprises a
metal sleeve surrounded by said elastomeric portion.
5. The suspension component connection assembly of claim
1 wherein said sleeveless bushing further comprises a
pin surrounded by said elastomeric portion.

0991359 080201
T02080 65E12660

6. The suspension component connection assembly of claim 1 wherein said bushing receiving bore has an inner diameter with a circumferential length and said groove portion of said suspension component extends substantially along the circumferential length of said inner diameter in its entirety.
7. The suspension component connection assembly of claim 1 wherein said bushing receiving bore has an inner diameter with a circumferential length and said groove portion of said suspension component extends along only a portion of said circumferential length of said inner diameter.

- 0921359.080201
Sub
a3
8. A suspension component connection assembly, comprising:

a suspension component having a bushing receiving bore with first and second opposing axial ends, said bushing receiving bore including a ribbed portion positioned intermediate said first and second axial ends of said suspension component; and

a sleeveless bushing having an elastomeric portion with first and second opposing axial ends, said elastomeric portion having a grooved portion positioned intermediate said first and second axial ends of said elastomeric portion, said ribbed portion being adapted to fit within said groove portion of said bushing.

9. The suspension component connection assembly of claim 8 wherein said suspension component comprises a leaf spring and said bushing receiving bore comprises a leaf spring eye.

10. The suspension component connection assembly of claim 8 wherein said suspension component comprises a shackle assembly.
11. The suspension component connection assembly of claim 8 wherein said sleeveless bushing further comprises a metal sleeve surrounded by said elastomeric portion.
12. The suspension component connection assembly of claim 8 wherein said sleeveless bushing further comprises a pin surrounded by said elastomeric portion.
13. The suspension component connection assembly of claim 8 wherein said bushing receiving bore has an inner diameter with a circumferential length and said ribbed portion of said suspension component extends substantially along the circumferential length of said inner diameter in its entirety.
14. A suspension component connection assembly, comprising:
a suspension component having a bushing receiving bore with first and second opposing axial ends, said bushing receiving bore including a slot portion positioned intermediate said first and second axial ends of said suspension component; and
a sleeveless bushing having an elastomeric portion with first and second opposing axial ends, said elastomeric portion having a protrusion positioned intermediate said first and second axial ends of said elastomeric portion, said protrusion being adapted to fit within said slot of said suspension component.

0921359 0880" 65ET2660

File at

15. The suspension component connection assembly of claim 14 wherein said suspension component comprises a leaf spring and said bushing receiving bore comprises a leaf spring eye.
16. The suspension component connection assembly of claim 14 wherein said sleeveless bushing further comprises a metal sleeve surrounded by said elastomeric portion.
17. The suspension component connection assembly of claim 14 wherein said sleeveless bushing further comprises a pin surrounded by said elastomeric portion.
18. A suspension component connection assembly, comprising:
a suspension component having a bushing receiving bore with first and second opposing axial ends, said bushing receiving bore including a hole positioned intermediate said first and second axial ends of said suspension component; and
a sleeveless bushing having an elastomeric portion with first and second opposing axial ends, said elastomeric portion having a protrusion positioned intermediate said first and second axial ends of said elastomeric portion, said protrusion being adapted to fit within said hole of said suspension component.
19. The suspension component connection assembly of claim 18 wherein said suspension component comprises a leaf spring and said bushing receiving bore comprises a leaf spring eye.

0992359.080201
T02080"65522660

20. The suspension component connection assembly of claim 18 wherein said sleeveless bushing further comprises a metal sleeve surrounded by said elastomeric portion.
21. The suspension component connection assembly of claim 18 wherein said sleeveless bushing further comprises a pin surrounded by said elastomeric portion.

FOIA b 7 - DATED 08/20/01